

Conventional Flame Detector

DRD-E



Features

- ▶ Class 1 performance as defined in BS EN54-10:2002 (range up to 25 m)
- ▶ Single IR technology
- ▶ Robust and slim design
- ▶ Low current consumption
- ▶ Easy to install
- ▶ Fits any of the CDX Range of mounting bases
- ▶ Twin LEDs for 360° view
- ▶ Approved by LPCB & VdS

Description

The DRD-E is a flame detector designed for internal use to detect large flames. The detector fits any of the CDX range of mounting bases. The detection zone is a 90° cone and the detection range is up to and including 25 m.

Specification	
Ordering code	DRD-E
Current consumption @ 24Vd.c.	Quiescent 70 µA, Alarm 40 mA
Surge current	320 µA
Minimum alarm trip current	6 mA
Voltage range	15 – 30 V dc
IP rating	IP42
Operating temperature range	-10 °C to +50 °C
Classification	Class 1 EN54-10:2002
Detection zone	90° cone
Detection range (max)	25 m
Compatible CDX bases	YBN-R/6, YBO-R/6PA, YBO-R/6R, YBO-R/6RN, YBO-R/6RS, YBN-R/6SK
Colour	Ivory
Weight (g) / Dimensions (mm)	124 / 100 diameter x 37.3 height